



MAINTENANCE SPECIFICATIONS

SPEC



Model	PZ500ML
<p>Slide rail suspension:</p> <p style="padding-left: 20px;">Rear travel</p> <p style="padding-left: 20px;">Suspension spring rate</p> <p style="padding-left: 40px;">Front</p> <p style="padding-left: 40px;">Rear</p> <p style="padding-left: 20px;">Spring wire diameter</p> <p style="padding-left: 40px;">Front</p> <p style="padding-left: 40px;">Rear</p>	<p>274 mm (10.79 in)</p> <p>14.7 N/mm (1.5 kg/mm, 84 lb/in)</p> <p>22.6 ~ 42.2 N/mm (2.3 ~ 4.3 kg/mm, 129 ~ 241 lb/in)</p> <p>∅7.8 mm (0.31 in)</p> <p>∅10.6 mm (0.42 in)</p>
<p>Suspension setting position:</p> <p style="padding-left: 20px;">Stopper band hole position (F)</p> <p style="padding-left: 20px;">Hook setting length*</p> <div style="text-align: center; margin: 5px 0;">  </div> <p style="padding-left: 20px;">Full rate adjusting position**</p> <div style="text-align: center; margin: 5px 0;">  </div>	<p>No.1</p> <p>10 mm (0.39 in)</p> <p>B</p>
<p>Shock absorber damping force:</p> <p style="padding-left: 20px;">Front</p> <p style="padding-left: 40px;">Extension</p> <p style="padding-left: 40px;">Compression</p> <p style="padding-left: 20px;">Rear</p> <p style="padding-left: 40px;">Extension</p> <p style="padding-left: 40px;">Compression</p>	<p>500 N/0.3 m/s (51 kg/0.3 m/s, 113 lb/0.3 m/s)</p> <p>1,735 N/0.3 m/s (177 kg/0.3 m/s, 391 lb/0.3 m/s)</p> <p>1,451 N/0.3 m/s (148 kg/0.3 m/s, 327 lb/0.3 m/s)</p> <p>804 N/0.3 m/s (82 kg/0.3 m/s, 181 lb/0.3 m/s)</p>
<p>Slide runner:</p> <p style="padding-left: 20px;">Thickness</p> <p style="padding-left: 20px;">Wear limit</p>	<p>17.8 mm (0.70 in)</p> <p>10 mm (0.39 in)</p>
<p>Track sprocket wheel:</p> <p style="padding-left: 20px;">Material</p> <p style="padding-left: 20px;">Number of teeth</p>	<p>Polyethylene</p> <p>8T</p>
<p>Rear guide wheel:</p> <p style="padding-left: 20px;">Material</p> <p style="padding-left: 20px;">Outside diameter</p>	<p>High molecular weight polyethylene with rubber</p> <p>158 mm (6.16 in)</p>
<p>Brake:</p> <p style="padding-left: 20px;">Pad thickness</p> <p style="padding-left: 20px;">Pad wear limit</p> <p style="padding-left: 20px;">Disc outside diameter</p> <p style="padding-left: 20px;">Disc thickness</p>	<p>13 mm (0.51 in)</p> <p>7.5 mm (0.29 in)</p> <p>220 mm (8.66 in)</p> <p>5.0 mm (0.20 in)</p>